

UNDER-COUNTER POU SYSTEM FOR ARSENIC REDUCTION

The DWS-2S-2710-02 is a dual stage water treatment approach with an integrated system design, ideal for under-counter household use. The system includes two selected 2.75 x 9.75 inch arsenic removal cartridges, housing components, i.e., sumps, caps, mounting bracket, faucet (lead-free), shut-off device, and tubing for a complete unit. AdEdge Water Technologies, LLC supplies both the system components and replacement cartridges. The system is available to qualified water treatment distributors and dealers for subsequent re-sale to end users. Replacement cartridges are available through AdVantEdge authorized distributors.



SPECIFICATIONS - MODEL DWS-4510-02

| | |
|----------------------|---|
| Filtration Cartridge | Two 10 inch standard (2.75 x 9.75 inch); AdVantEdge Model AD2710S |
| Materials Housing | Injection molded polypropylene |
| Mounting | Painted metal mounting bracket |
| Faucet | Lead-free faucet with 1/4 inch tubing |
| Shut Off Device | Mechanical countdown shut-off device mounted on bracket |
| Arsenic Media | Bayoxide® E33 |
| Water Source | Potable water of known microbiological quality (microbiologically safe) |
| NSF Testing | Components tested in accordance with NSF protocols, no specific listings |
| Box/Packaging | Plain white box, with or without label |

Performance

| | |
|-----------------------|---|
| Rated Cartridge Life | 1000 gallons |
| Arsenic concentration | Up to 50 ppb influent arsenic |
| Replacement | Every 12 months or 1000 gallons, whichever comes first |
| Rated Flow Rate | 0.5 gpm |
| Parameters | AD2710S - Arsenic |

Note:

Bayoxide® E33 is a registered trademark of LANXESS Deutschland GmbH.