

MBG-25098-05

Grooved Polypropylene Sediment Cartridges



NSF
COMPONENT
Tested and certified by NSF International against NSF/ANSI Standard 42 for material safety only.



Residential / Commercial Filtration Applications

Standard Features

- Manufactured in China
- Dependable and cost-effective solution for pre-filtration for the food and beverage industry
- Grooves create increased surface area for longer cartridge life and high dirt-holding capacity
- Melt blown polypropylene filter media
- Provides excellent prefiltration in reverse osmosis systems, UV systems, and beverage filtration systems
- Filters for particulates, sediment, dirt, and rust

Product Specifications

Filter Media

Polypropylene

Micron Rating (Nominal)

5 microns

Dimensions

2-1/2" diameter x 9-7/8", 2-1/2" diameter x 20"

Cartridge Style

Drop-In

Operating Temperature

40° F to 145° F (4.4° C to 62.8° C)

Maximum Pressure Drop

69° F (20° C) 46.4 psi (3.2 kg/cm²)

Recommended Replaceable Pressure Drop

21.75 psi (3.2 kg/cm²)

Maximum Flow

7 gpm/14 gpm

Case Pack

25 per case (9-3/4"), 25 per case (20")

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Applications

- 1 Beverages
- 2 Electronics
- 3 Fine Chemicals
- 4 Plating Solutions
- 5 Potable Water
- 6 Prefiltration for Reverse Osmosis

Distributed By:



2299 Ridge Rd., Greenville, SC
P: 888.859.1188 · F: 864.284.1819
NeoLogicSolutions.com · Info@NeoLogicSolutions.com

Questions?

Ask our Service Representatives at:
888.859.1188 Mon.-Fri. 8a-8p,
Sat 8:30a-4:30p EST.