## **SDG-45 Series** 25 Micron Sediment Depth Grooved Cartridges



# neo-pure

### Residential/Commercial Filtration Applications

## **Standard Features**

- Manufactured in China
- Rigid construction holds up to heavy water pressure conditions
- Grooves create increased surface area for longer cartridge life and high dirt-holding capacity compared to non-grooved polypropylene filters
- Melt blown polypropylene filter media
- Porous cylinder inside the filter traps sediment, dirt and rust efficiently without affecting the water flow

## **Product Specifications**

#### Filter Media

Polypropylene

#### Micron Rating (Nominal)

25 microns

Dimensions 4-1/2" dia. x 20"


Cartridge Style Drop-In

#### **Operating Temperature** 100°F (37.78°C)

Pressure Rating

Up to 125 psi

Maximum Flow Rate 45 gpm



#### Case Pack

12 per case (10BB), 6 per case (20BB)

#### WARNING:

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.



9450 SW Gemini Dr, ECM #83358, Beaverton, OR 97008 Tel 855.896.3525 · Fax 866.409.9622 www.neologicsolutions.com · info@neologicsolutions.com STUART. FL · BEAVERTON. OR · GREENVILLE, SC · SAN DIEGO. CA

#### **QUESTIONS?**

Ask one of our Service Representatives: Mon-Fri 8a-8p, Sat 8:30a-4:30p EST



© Copyright 2014 NeoLogic Solutions. All Rights Reserved. Manufacturer reserves the right to make changes without notice.

ne system.